


# BOMAG

## TANDEM VIBRATORY ROLLERS BW 100 AD-4, BW 120 AD-4, BW 125AD-4

### PERFORMANCE DATA



Machine type	Compaction output (m <sup>3</sup> /h) at recommended soil layer thicknesses		
	Gravel, sand	Mixed soil	Silt, clay
BW 100 AD-4	80-145	55-105	38-73
BW 120 AD-4	85-170	65-125	43-85
BW 125AD-4	90-185	70-140	50-95

Machine type	Compaction output (t/h) at different asphalt layer thicknesses		
	2-4 cm	6-8 cm	10-12 cm
BW 100 AD-4	15-40	40-60	60-100
BW 120 AD-4	20-45	40-70	70-120
BW 125AD-4	25-50	45-80	75-130

# BOMAG

# Technical Data

Shipping dimensions in m3	without ROPS	with ROPS
BW 100 AD-4	4,794	6,591
BW 120 AD-4	5,685	7,816
BW 125AD-4	5,685	7,816


## Standard Equipment

- Oscillating artic. center joint
- 2 scrapers per drum
- Suspended operator's platform
- Plastic water tank
- Hour meter
- Lockable engine cover
- Lockable anti vandal dashboard protection
- Transport lashing and lifting points front/rear
- Emergency stop button
- Vibration cut-off, rear drum
- Back-up alarm
- Water level
- Gravity water sprinkler system

## Optional Equipment

- \* ROPS with safety belts
- \* Working lights front/rear
- \* Seat with contact switch
- Edge cutter
- Indicator and hazard lights
- Rotary beacon
- Biodegradable hydraulic oil
- Special paint
- Tool kit
- Double travel lever (Sliding seat)
- Foldable ROPS
- Laterally sliding seat
- Fuel level indicator
- Single point lifting device
- Pressure sprinkler system
- Electronic Engine Immobilizer
- Weather protection cabin
- Battery disconnect switch
- Document bag
- Sun roof
- Flow divider

\* Standard delivery with CE conformity (valid within European Union)



## Dimensions in mm

	A	B	C	D	H	H2	K	L	O	S	W
BW 100 AD-4	1728	1076	475	700	1800	2475	255	2475	38	13	1000
BW 120 AD-4	1728	1276	474	700	1800	2475	255	2475	38	13	1200
BW 125AD-4	1728	1276	474	700	1800	2475	255	2475	38	23	1200

## Technical Data

Technical Data	BOMAG BW 100 AD-4	BOMAG BW 120 AD-4	BOMAG BW 125AD-4
----------------	-------------------	-------------------	------------------

## Weights

Operating weight w. ROPS CECE	kg	2.400	2.600	3.150
Average axle load CECE	kg	1.200	1.300	1.575
Average static linear load CECE	kg/cm	12	10,8	13,1

## Dimensions

Length with ROPS	mm	2.475	2.475	2.475
Track radius, inner	mm	2.720	2.620	2.620

## Driving Characteristics

Max. working speed with vibration	km/h	0- 6,5	0- 6,5	0- 6,5
Max. travel speed	km/h	0- 12,0	0- 12,0	0- 12,0
Max. gradeability without/with vibr.	%	40/30	40/30	40/30

## Drive

	BOMAG BW 100 AD-4	BOMAG BW 120 AD-4	BOMAG BW 125AD-4
Engine manufacturer	Kubota	Kubota	Kubota
Type	D 1703-M-E3B	D 1703-M-E3B	D 1703-M-E3B
Cooling	water	water	water
Number of cylinders	3	3	3
Performance ISO 9249	kW	24,7	24,7
Performance SAE J 1349	hp	33,1	33,1
Speed	min-1	2.600	2.600
Speed adjustment 1	min-1	2.400	2.400
Speed adjustment 2	min-1	2.600	2.600
Electric equipment	V	12	12

## Brakes

Service brake	hydrost.	hydrost.	hydrost.
Parking brake	hydromec.	hydromec.	hydromec.

## Steering

Steering system	oscil.artic.	oscil.artic.	oscil.artic.
Steering method	hydrost.	hydrost.	hydrost.
Steering angle +/-	grad	30	30
Oscillating angle +/-	grad	7	7

## Exciter system

Vibrating drum	front + rear	front + rear	front + rear
Drive system	hydrost.	hydrost.	hydrost.
Frequency	Hz	70/55	70/55
Amplitude	mm	0,49	0,40
Centrifugal force	kN	37/23	45/28


## Sprinkler System

Type of sprinkling	gravity	gravity	gravity
--------------------	---------	---------	---------

## Capacities

Fuel	l	40	40	40
Water	l	220	220	220

Technical modifications reserved. Machines may be shown with options



PRE 880 00 001

210808 Sa05

**BOMAG**  
Hellerwald  
D-56154 Boppard  
P.O. Box 5162  
Tel. (0)6742 - 1000  
Fax (0)6742 - 3090  
Fax (0)6742 - 3090

# BOMAG